



G22018L

DUHS Hospital unit - left-hand drainer

DUHS hospital disposal unit left hand drainer without tap holes or overflow, for duct mounted cisterns. Manufactured from 1.2mm thick, grade 1.4301 (304) stainless steel with a satin polish finish. The top is turned down on all four edges and incorporates a wet area recess. Fitted with a 110mm diameter outlet sluice hopper at one end which can accept a P or S trap, (available as an extra). A bowl, without waste, is positioned next to the sluice hopper and is prepared for a

38 mm waste outlet. The unit should only be fed from a cistern or tank water supply, a 9 litre capacity plastic cistern is available as an extra. Mounted on either stainless steel cantilever brackets or front leg supports with adjustable feet, which give a working height of 900mm. Manufactured in accordance with HTM 64 / HBN 00-10, Part C Standards.

Technical data

| | |
|---------------------------|--------------------------------|
| Bowl - bowl depth | 200mm |
| Bowl finish | Satin finish |
| Bowl depth | 400mm |
| Bowl width | 500mm |
| Drainer position | Left |
| Drainer or storage | Drainer |
| Gross weight | 18.10kg |
| Material | Stainless steel |
| Material code | 1.4301 chrome nickel steel V2A |
| Material thickness | 1.2mm |
| Minimum flushing capacity | 6 litre |
| Outlet size | DN 100 |
| Overall depth | 600mm |
| Overall height | 300mm |
| Overall width | 1,600mm |
| Overflow | No |
| Surface finish | Satin finish |
| Tap ledge | No |
| Type of mounting | Wall and floor mounting |
| Waste hole position | Centre back |
| Waste hole projection | 225mm |
| Waste size | DN 32 |
| Net weight | 16.9kg |

KWC

DUHS Hospital unit

Optional accessories



Optional accessories

F1074N
Lever operated pillar tap



Optional accessories

F1075N
Lever operated mixer tap