



F5SM2020

Stainless steel shower panel

F5S Mix shower panel made of stainless steel for wall mounting with DN 15 self-closing single control mixer and connecting nozzles for the shower head. FRAMIC self-closing mixing cartridge, hydraulically controlled, low maintenance and stagnation free, with ceramic disc technology, self-closing, flow pressure independent due to the medium-independent design.

Stepless adjustment of flow duration. With adjustable, turn-proof temperature stop. For connection to hot water and cold water.

Technical data

Overall depth	90mm
Overall height	1.160mm
Overall width	235mm
Type of mounting	Wall mounting
Type of operation	Manual operation
Diameter nominal	DN 15
Inlet size	G 1/2 A
Material casing	Stainless steel
Material fitting	Brass
Type of mixing	With mixing
Sound insulation	No
Surface finish fitting	Chrome
Minimum flow pressure	1.5 bar
Volume flow rate at 3 bar	0.15 litre per second
Adjustable flow time	Yes
Functional principle	Hydraulic self-closing
Protective shutdown	No
Thermal disinfection	No
Additional connections	No
Circulation	No
Shower pipe draining	No
Type of shower	Shower panel
Position of water connection	From top / backside
Material code casing	1.4301 chrome nickel steel V2A
Surface finish casing	Satin finish
Maximum flow time	35 seconds
Minimum flow time	5 seconds

KWC

Stainless steel shower panel

Mandatory accessories



Mandatory accessories

SHAS0011

Slimline shower head

Mandatory accessories

SHAC0011

Comfort shower head