



Safe Breeze Hand Dryer (ALSSB15) by Anti Ligature Shop



Safe Breeze hand dryer, surface mounted ligature resistant

With compact dimensions in all directions, including a depth of just 10cm, this high speed, adjustable hand dryer is perfect for even the smallest of washrooms. With the ability to be run at just 350W, yet overall rated power on maximal settings being just 1KW, this really is a great energy efficient hand dryer. We would recommend this hand dryer be used in locations that will receive up to 300 uses a day

It has the ability to reduce noise by reducing motor speed, as well as being able to turn the heater element on or off. This is a great addition as you can keep it at its most energy efficient in the warm months, yet add heat to the airflow if necessary. Built with a strong anti-vandal casing and fast airflow, created using dual air outlets to maximise

Tough steel cover maximises protection of the internal unit. A depth of 10cm makes this a very compact unit. A solid 29,000 RPM motor produces an air speed of up to 183MPH, which produces a manufacturer stated dry time of 10-15 seconds. The motor is adjustable from 500W to 350W and the 500W heater element can be switched on or off, giving a rated power range between 0.35kW and 1kW. Noise levels are stated as being between 72.8 and 77.6 db at 1m. Three safety protections prevent overheating and continuous running

Specification

Electrical Supply Voltage	220-240 Volts	Rated Power (max settings)	1000 Watts
Electrical Supply Frequency	50 / 60 Hz	Rated Power (min settings)	350 Watts
Standby Power Consumption	0.3 - 0.4 Watts	Heater Element Power	500 Watts
Expected Motor Life	1500 Hours	Operating Sound Level (max)	78 dB*
Dry Time (max setting)	10 - 15 Seconds*	Operating Sound Level (min)	73 dB*
Universal Brush Motor		Sensor type	IR
Motor Speed (max setting)	29,000 RPM	Guarantee	2 years
Air Speed (max setting)	183 MPH	Materials	White epoxy on steel, Polished stainless steel
Air Speed (min setting)	156 MPH	Net Weight	3.5kg
Air Volume (max setting)	60 CFM	Packed Weight	4.5kg
Air Volume (min setting)	41.7 CFM	IP rating	IP24
Motor Cutoff Time	60 Seconds	Product Height	216mm
Motor Class	Class I	Product Width	276mm
		Product Depth	100mm
Certifications	CE, UL, ROHS, GS, LVD, EMC, CB, GreenSpec		

NBS Specification

The anti-ligature design features of this product are not intended to replace or substitute the need for necessary supervision of those who may be at risk, or for other necessary protective measures to be taken in the specific circumstances of usage. Anti-Ligature Shop does not claim any product to be totally ligature free or make claim that they cannot be damaged with regard to anti-vandal feature. It is therefore the customers responsibility to ensure the suitability of the product for the environment in which they are to be fitted.



Contact enquiries@lig-safe.co.uk for any specific training / testing requirements.

